

SR-8040BP

Bipolar surround loudspeaker

0 reviews with an average of 0/5

AVAILABLE FINISHES: 



Overview

- The perfect surround speaker for BP SuperTower® series front speakers
- Bipolar dispersion pattern (speakers on front left and front right sides) for totally enveloping surround sound that puts you in the action
- The same highest quality components as Definitive's front channel speakers for seamless channel to channel transition
- Two 3-1/2 inch die cast basket patented BDSS drivers and two 1 inch pure aluminum dome tweeters
- Easy wall mount system included

The SR-8040HD is built to the same high performance standards as Definitive's main left and right front speakers and includes features like high-definition second generation patented BDSS bass/midrange drivers with butyl rubber surrounds, wide-dispersion pure aluminum dome tweeters, complex crossover networks and rock-solid cabinet construction. It can be mounted to a wall with the integrated keyhole plate or it can be placed atop a shelf or after-market stand. However you use the SR-8040BP you'll enjoy superior surround sound realism.

The Bipolar Advantage

Definitive's SR-8040HD is a bipolar system containing two complete full-range speaker systems, one on each side of the cabinet. Bipolar radiation spreads the surround signals evenly throughout your room for a more enveloping sense of you-are-there realism than could be achieved with conventional forward-firing speakers.

The SR-8040HD is a full-range, extremely linear, low-distortion system which is timbre-matched to blend perfectly with all Definitive BP series speakers as well as other high-quality speaker systems. The SR-8040HD wide dynamic range, high-definition sound quality and its bipolar radiation pattern results in total immersion in the musical event or movie soundstage.

Bipolar Surrounds are Easy to Use

Definitive's bipolar surrounds are designed for easy and unobtrusive placement in your room. Easy-to-use mounting plates are included for wall mounting. Definitive's BP surround speakers may be located on the sides or rear of the room (or both as in 6.1 and 7.1 channel installations) with excellent results.

Patented Technology Delivers High Definition and Wide Dispersion

Dispersing the surround channel sound evenly over a broad area of the room is vital for creating the enveloping you're-in-the-action experience movie directors intend for you to experience. We've engineered the SR models with our latest generation ultra-high definition midrange drivers that set new standards for wide dispersion and clean, accurate reproduction.

The drivers used in the SR-8040BP are 3-1/2" second generation BDSS drivers. BDSS is Definitive's patented Balanced Double Surround System technology that supports the speaker cone at both the inner and outer edges allowing longer, more linear excursion for greater clarity and finely textured inner detail. A new patent pending Linear Response Waveguide™ smoothes off-axis frequency response and disperses sound over a wider area for crystal clear intelligibility and life-like envelopment for every listener in the room. The tweeters are pure aluminum domes, which has been heat-treated to relax the crystal structure and then coated with a ceramic to produce extended highs that reveal nuance and shimmer without a trace of edginess.

The Proof is in the Listening

Now that you're thoroughly impressed with the technology and passion we've poured into the SR-8040BP it is time to find a stocking dealer near you to audition this remarkable achievement of art and science.

[Find a retailer near you](#)

Watch the SR series video:

Product Specifications

Driver Complement

Tweeter

Quantity	2
Diameter	1" (2.54cm)
Type	Pure Aluminum Dome

Mid / Woofer

Quantity	2
Diameter	3 1/2" (8.89cm)
Type	BDSS 2nd Generation

Tweeter/Mid Array

Type	Front Facing Bipolar Configuration
------	------------------------------------

Electrical

Audio Inputs

Speaker Level	1 Pair (Speaker Cable)
---------------	------------------------

Maximum Sensitivity

1 watt @ 1 Meter	92 dB
------------------	-------

Electrical

Total Frequency Response

Overall 50 Hz - 30 kHz

Nominal Impedance

Compatible with 8 ohm

Crossover

A/V Receiver Crossover Setting Small (100 Hz)

Power Handling 20 - 150 watts per channel

Installation

Placement

Vertical Orientation On Wall or On Shelf

Mounting

Flush-Mount Wall Bracket Included

Product Weight

Out of Box 8 lbs

Dimensions

Cabinet Dimensions

Height 9 1/2" (24.13cm)

Width 7 13/16" (19.84cm)

Depth 5 3/8" (13.65cm)

Shipping

Accessories

Included Accessories Keyhole Hanger

Carton Size

Height 11 13/16" (30.00cm)

Width 7 5/16" (18.57cm)

Depth 9 7/8" (25.08cm)

Shipping Weight

One per Carton 10 lbs

Warranty

Drivers and Cabinet

Parts and Labor 5