

SuperCube 6000

NEW! High performance powered subwoofer

[★★★★★4.7 out of 5 stars. Read reviews.](#)

[4.7 out of 5 rating.4.7](#)

(3)

Write a review. This action will open a modal dialog.

Ask a question

AVAILABLE FINISHES:



[Printer friendly page](#)



-
-
-
-





- [Overview](#)
- [Specs](#)
- [Videos](#)
- [Literature](#)
- [Owner Reviews](#)

Driver Complement

Subwoofer

Quantity	1
Diameter	9" (22.86cm)
Type	High Excursion Active Subwoofer Driver

Bass Radiator

Quantity	2
Diameter	10" (25.40cm)
Type	Planar Low Bass Radiator

Control

Display

Alpha Numeric Display	Disappearing
-----------------------	--------------

Remote Control

IR Control	Performance Optimizer Remote (Included with Subwoofer)
Functionality	Volume; Mute; Low Pass Filter; Night Mode; Phase; EQ; Display

Digital Signal Processing

56 bit DSP	User Selectable
------------	-----------------

Digital Crossover

Control

Low Pass Filter	40 - 150 Hz, variable in 5 Hz increments
-----------------	--

Low Pass Filter Slope	12 dB per Octave
-----------------------	------------------

Digital Phase Control

Phase Settings	0, 90, 180, 270 or 360 degrees
----------------	--------------------------------

Electrical

Wireless Capability

Wireless Capability	Wireless Ready
---------------------	----------------

Audio Inputs

LFE input	1 (RCA)
-----------	---------

Speaker Level	2 Pair (Speaker Cable)
---------------	------------------------

Stereo Line Level	2 (RCA)
-------------------	---------

Total Frequency Response

Overall	14 Hz - 200 Hz
---------	----------------

Amplifier

Internal Amplifier

Power	1500 watts
-------	------------

Channels	1
----------	---

Type	Class HD
------	----------

Protection Circuitry

Primary	Multiband Dynamic Range Optimizer (M-DRO)
---------	---

Secondary	Thermal Overload Sensor
-----------	-------------------------

Power Cycle

US	Auto On/Off: Signal Sensitive (defeatable)
----	--

Amplifier

International

Auto On/Off: Signal Sensitive
(defeatable)

Power Requirements

US

110 volts A/C

International

220 volts A/C

Fuse

US

6.2 amp 250 volt Slo Blo

International

4 amp 250 volt Slo Blo

Dimensions

Cabinet Dimensions

Height

12 7/8" (32.70cm)

Width

12" (30.48cm)

Depth

13" (33.02cm)

Depth with Wireless Module

14" (35.56cm)

Shipping

Accessories

Included Accessories

Performance Optimizer Remote; Rubber Feet (4); Spikes (4)

Optional Accessories

SCW-100 Wireless Kit (Available Separately)

Carton Size

Height

17" (43.18cm)

Width

16" (40.64cm)

Depth

16 1/2" (41.91cm)

Shipping Weight

Shipping

One per Carton

43 lbs

Warranty

Electronic Components

Parts and Labor

3

Drivers and Cabinet

Parts and Labor

5