

SuperCube 8000

NEW! Ultra-performance powered subwoofer

[★★★★★★★★4 out of 5 stars. Read reviews.](#)

[4 out of 5 rating.4.0](#)

(2)

Write a review. This action will open a modal dialog.

Ask a question

AVAILABLE FINISHES:



[Printer friendly page](#)



-
-
-
-





- [Overview](#)
- [Specs](#)
- [Videos](#)
- [Literature](#)
- [Owner Reviews](#)

Driver Complement

Subwoofer	
Quantity	1
Diameter	11" (27.94cm)
Type	High Excursion Active Subwoofer Driver
Bass Radiator	
Quantity	2
Diameter	12" (30.48cm)
Type	Planar Low Bass Radiator

Control

Display	
Alpha Numeric Display	Disappearing
Remote Control	
IR Control	Performance Optimizer Remote (Included with Subwoofer)
Functionality	Volume; Mute; Low Pass Filter; Night Mode; Phase; EQ; Display

Control

Digital Signal Processing

56 bit DSP	User Selectable
------------	-----------------

Digital Crossover

Low Pass Filter	40 - 150 Hz, variable in 5 Hz increments
-----------------	--

Low Pass Filter Slope	12 db per Octave
-----------------------	------------------

Digital Phase Control

Phase Settings	0, 90, 180, 270 or 360 degrees
----------------	--------------------------------

Electrical

Wireless Capability

Wireless Capability	Wireless Ready
---------------------	----------------

Audio Inputs

LFE input	1 (RCA)
-----------	---------

Speaker Level	2 Pair (Speaker Cable)
---------------	------------------------

Stereo Line Level	2 (RCA)
-------------------	---------

Total Frequency Response

Overall	12 Hz - 200 Hz
---------	----------------

Amplifier

Internal Amplifier

Power	1500 watts
-------	------------

Channels	1
----------	---

Type	Class HD
------	----------

Protection Circuitry

Primary	Multiband Dynamic Range Optimizer (M-DRO)
---------	---

Amplifier

Secondary

Thermal Overload Sensor

Power Cycle

US

Auto On/Off: Signal Sensitive
(defeatable)

International

Auto On/Off: Signal Sensitive
(defeatable)

Power Requirements

US

110 volts A/C

International

220 volts A/C

Fuse

US

6.2 amp 250 volt Slo Blo

International

4 amp 250 volt Slo Blo

Dimensions

Cabinet Dimensions

Height

16 1/4" (41.27cm)

Width

15 1/4" (38.73cm)

Depth

16" (40.64cm)

Depth with Wireless Module

17" (43.18cm)

Shipping

Accessories

Included Accessories

Performance Optimizer Remote; Rubber
Feet (4); Spikes (4)

Optional Accessories

SCW-100 Wireless Kit (Available
Separately)

Carton Size

Height

21 3/4" (55.24cm)

Shipping

Width	21" (53.34cm)
-------	---------------

Depth	20 7/8" (53.02cm)
-------	-------------------

Shipping Weight

One per Carton	75 lbs
----------------	--------

Warranty

Electronic Components

Parts and Labor	3 Years
-----------------	---------

Drivers and Cabinet

Parts and Labor	5 Years
-----------------	---------