

## TANNOY MERCURY 7.4



Suitable for larger listening rooms or where high volumes are required, Mercury 7.4's 44 litre twin-ported cabinet, dual 178 mm (7 inch) mid/bass drivers and refined 28 mm (1.1 inch) soft dome tweeter pack a mighty punch.

To further enhance imaging and produce the widest soundstage, the drivers are positioned in a D'Appolito driver configuration. By placing the tweeter centrally between the two bass/mid drivers, the speaker's dispersion characteristics are smoothed through the critical crossover region resulting in a highly articulate musical performance on or off the loudspeaker's main axis. This eliminates the traditional 'sweet spot' to deliver peak performance across more seats in your listening room.

As befits a flagship of any TANNOY loudspeaker series, the Mercury 7.4 boasts class leading peak power handling at 300 Watts and extremely high 93 dB/Watt efficiency making it suitable for the broadest range of partnering equipment.

## FEATURES

- 2 way floorstanding loudspeaker for medium to large sized rooms.
- 2 x 7" mid/bass driver offers a powerful performance from a compact cabinet.
- 1.1" coated silk dome extends high frequency response to 32 kHz providing fine vocal and instrumental detail.
- Light yet stiff multi-fibre coated paper pulp cone delivers fast, tight and punchy bass reproduction.
- 6 point driver fixing and aesthetically coordinated HF faceplate provides modern technical styling.
- Black oak vinyl finish to enhance home décor.
- High tolerance crossover components provide smooth integration across frequency bandwidth.
- Silver plated wiring and DMT (Differential Materials Technology) damping on HF capacitor enhance musicality and communication.
- Crossover and internal damping tuned to ensure superb leading edge attack of drums and bass instruments.
- High power handling allows speakers to be driven hard yet remain subtle and refined at everyday listening levels.
- Heavyweight fiberboard construction with extensive internal bracing enhances the effortless full-bodied sound.
- Cabinets ported for a richer and deeper bass response
- Adjustable floor spikes allow precise leveling of speaker cabinet without damage to carpets.
- Dedicated plinth provides stability to deliver tighter and faster bass response.
- 10-Year Warranty Program\*
- Designed and engineered in the U.K.

## SPECIFICATIONS

**Performance:** Recommended amplifier power (Watts RMS): 20 – 150  
Continuous power handling (Watts RMS): 75  
Peak power handling (Watts): 300  
Sensitivity (2.83 Volts @ 1m): 93  
Nominal Impedance (Ohms): 8  
Frequency response (-6 dB): 32 Hz – 32 kHz

**Drive Units:** High frequency: 28 mm (1.1") Nitro-urethane damped layer woven polyester dome, Neodymium magnet system.

Low frequency: 178 mm (7") Multi- fibre coated pulp paper cone x 2

**Crossover:** Crossover Frequency: 2.4 kHz  
Crossover Type: Passive low loss 2nd order low pass, 3rd order high pass, bi-wired

**Construction:** Enclosure type: Twin rear ported reflex  
Volume: 44.0 l (1.55 cu. ft)  
Dimensions (H x W x D): 955 x 314.3 x 308 mm  
(inc plinth - 37.6 x 12.4 x 12.1")  
Net weight: 15.0 kg (33.1 lbs)